



RUST-X GREASE MP-3 WITH EP ADDITIVES

PRODUCT DESCRIPTION :

These are multi-functional performance greases processed from well refined and low volatile mineral oils and thickened with Lithium soap. **Multipurpose greases** have good shear stability, surface adhesion and thus resistant to wear, dust, dirt, corrosion and oxidation. These are suitable for automotive and industrial purpose and operating at temperatures ranging from 20 degrees centigrade to 120 degrees centigrade.

Multipurpose greases are recommended for the use in generator bearings, universal joints bearings, journal bearings, heavy loaded trucks and contractor / construction equipment's. Also for antifriction, ball and roller bearings found in farm equipment's, crane and shovel bearings in contractor equipment's.

Multipurpose grease is water resistant and not compatible with soda or such other grease and hence the bearings have to be thoroughly cleaned before packing with this grease.

PRODUCT SPECIFICATION :

1. Soap base	Lithium
2. Texture	Smooth, buttery
3. Worked penetration @ 25 C 60 / 60 strokes	220 – 250
4. Difference between work and unworked penetration	20
5. Free organic acidity as oleic % mass max.	0.2
6. Free alkalinity as LiOH % mass max	0.2
7. Drop point min. C	180
8. Copper corrosion	Negative
9. % with oil separation on storage 18 hrs. @ 40 deg. C	4.0 max
10. Oxidation Stability	
drop in pressure kg. f / cm 2, (100 hrs.)	0.5 max.
11. Kinematics Viscosity @ 100 deg. C cst	9-13

RUST-X

REST WITHOUT RUST

T.A. C.KNOOP, AUSTRALIA

for longer life